

ALPHA PLAST WP-170

Integral Waterproofing Admixture for Concrete

ALPHA PLAST WP-170

Integral Waterproofing Admixture for Concrete

DESCRIPTION:

ALPHA PLAST WP-170 High range water reducing admixture it is ideal for use in any concrete where it is desired to keep the water/cement ratio to a minimum and still achieve the degree of workability necessary to provide easy placement and consolidation.

ALPHA PLAST WP-170 does not contain calcium chloride or any other ingredients that would promote the corrosion of steel.

ALPHA PLAST WP-170 Lower water demand and increases slump without having slump loss associated with other Superplasticizers, enabling the water phase of the concrete to perform more effectively.

ALPHA PLAST WP-170 are ingredient other than water, aggregate and Portland cement that are added to a concrete mixture immediately prior to or during mixing.

USES:

ALPHA PLAST WP-170 A concrete admixture is a quick setting cement that can be used for several function for:

- ◆ To significantly reduce the water consumption of a concrete mix.
- ◆ Accelerate its setting time.
- ◆ Improve Workability.
- ◆ High strength concrete
- ◆ Long-distance traveling
- ◆ Low W/C ratio concretes

ADVANTAGES AND BENEFITS:

- ◆ Provide self-compacting concrete.
- ◆ Diminishing returns.
- ◆ Improve workability.
- ◆ Increased air content.
- ◆ Slow strength development.
- ◆ Reducing shrinkage.
- ◆ Concrete requires less vibrating.
- ◆ Non Staining
- ◆ Improves trowel ability and surface finish.

DOSAGE:

ALPHA PLAST WP-170 dosage range is from 0.08 to 1.60 liters/100 kg of cementitious material

DIRECTIONS FOR USE / APPLICATION:

ALPHA PLAST WP-170 can be added to the initial batch water or directly on the freshly batched concrete. However, better results have been observed batching directly on the freshly batched concrete. It should not come into contact with dry cement or other admixtures until mixed thoroughly with the concrete batch. **ALPHA PLAST WP-170** is dispensed with automatic equipment, thus insuring uniformity of admixture use throughout the job.

PROPERTIES:

Appearance	Dark Brown
Specific Gravity	Typically 1.145 @ 25°C
Chloride content	Nil to BS 5075 & BS:EN934-2
Air entrainment	Typically less than 2% additional air is entrained at normal dosages.
Alkali content	Typically less than 5.0 g. Na ₂ O Equivalent / litre of admixture.

STANDARDS:

ASTM C494	Type A & F
BS 5075	Part 1
WRC	Used in portable water

PACKING:

Supplied in	DRUM / IBC
Storage	Dry, Frost free, out of direct sunlight.
Shelf life	12 months, when stores as above
Hazard class	No dangerous goods. Observe Material Safety datasheet

COMPATIBILITY:

ALPHA PLAST WP-170 is compatible with all types of cement complying with international standards. It can be used in combination with the following admixtures and additives.

- ◆ Air entraining admixtures
- ◆ Anti-freezing admixtures
- ◆ Pozzolan (Micro silica, flyash, GGBFS)
- ◆ Synthetic fibers
- ◆ Alkali silica reaction control admixtures
- ◆ waterproofing admixtures